







SPECIFICATION

G

CONFIGURATIONS

UP TO 14 SASHES 90° CORNER SASH WITHOUT MULLION

SIGHTLINES 49MM SASH, 110MM SIGHTLINE

GLAZING MAX. 48 MM, MIN. 25 MM

MAXIMUM SASH DIMENSIONS WIDTH (L) 1200 MM, HEIGHT (H) 3000 MM

MAXIMUM SASH WEIGHT 120 KG

COLOUR

BFRC Rating

kWh/(m².yr)

0 to <10

-10 to <0

-20 to <-10

-30 to <-20

-50 to <-30

POWDER COATING RAL FINISH STANDARD 7016M, 9005M, 9016G AVAILABLE IN 150+ RAL FINISHES TEXTURED FINISH AVAILABLE SPLIT COLOR FOR INTERIOR/EXTERIOR WOOD EFFECT POWDER COATING ANODIZED ALUMINIUM

> A ++ A +

> > A

В

С

D

E



FEATURES

Transmittance

Acoustic insulation

Air permeability

Water tightness

Wind resistance

gimbal stabiliser

*

(((

≣

•

-

Uw ≥ 0.8 (W/m²K)

Rw up to 41 dB

Class 4

Class E750

Class C3

CONFIGURATIONS



DRAINAGE SUB SILLS



PROFILES WITH PRE-ASSEMBLED GASKET



Standard Sill Outer Frame



Glazing beads





HARDWARE





Regardless of whether you're looking to maintain modern aesthetics or a more traditional style, our choice of colours will suit you. We have a range of handle options to choose from to achieve the perfect look. The aluminium bifold plus that we supply at Glideline have been carefully designed to be thermally efficient. With a U-value of 1.0 W/m²K, your or your customer's home will be comfortable all year round.





GLIDELINE GO

KEEP UP TO DATE WITH YOUR GLAZING PROJECTS WITH GLIDELINE GO







Introducing GlidelineGO – the ultimate system designed to streamline your glazing order management process. With GlidelineGO, customers and trade partners can effortlessly create, track, and manage orders, while enjoying the convenience of approving drawings and making payments directly within the app.

Efficiency and ease-of-use are at the heart of GlidelineGO. Whether you're an architect, contractor, or glazing professional, this powerful app empowers you to take control of your glazing projects, ensuring a seamless experience from start to finish.



GLIDELNE